

## 12.5 LB EQUINE ONLY

LIGHTEST EQUINE GENERATOR ON THE MARKET

**JOB GREEN MACHINE 380HF**

COMPACT LIGHT AFFORDABLE

---

12.5 LBS



## HIGH FREQUENCY PORTABLE X-RAY UNIT

12.5 LB LIGHT-WEIGHT X-RAY MACHINE THAT IS DEPENDABLE, POWERFUL AND AFFORDABLE

**6 YEAR WARRANTY**

---

- APPROXIMATELY 5.7 kg OR 12.5 LBS,
- 4.92 IN (H) X 5.7 IN(W) X11.02 IN (L)
- 8 MEMORY SETTINGS
- DUAL DISTANCE LASERS PRESET AT 26"
- LOW VOLTAGE OPERATION POSSIBLE WITH AC 70 V.
- MODULAR CONNECTOR FOR DR SYSTEM COMPATIBILITY
- UP TO 80 kV AT 15 mA

**TELEVERE**

101 E. Milwaukee St. Ste. 405 Janesville, WI 53545 1.800.385.9593 **SYSTEMS**

# JOB GREEN MACHINE 380 HF

## LIGHTEST EQUINE GENERATOR ON THE MARKET

### SPECIFICATIONS

GENERATOR	Inverter control type, 1.26 kW output
KV SETTING	40-80 kV (1kV step). Rotary switch for digital display with 7 segment LED
mAs SELECTION	0.3-20 mAs* Rotary switch for digital display with 7 segment LED 0.3, 0.4, 0.5, 0.6, 0.8, 1.0, 1.3, 1.6, 2.0, 2.5, 3.2, 4.0, 5.0, 6.3, 8.0, 10, 13, 16, 20 mAs
X-RAY TUBE	A. Focal Spot: 0.8 mm X 0.8mm B. Anode heat storage capacity: 7kHU 9kJ(10kHU) C. Target angle: 16 degrees
TOTAL FILTRATION	2.5 mm Al EP. AT 80 Kv
COLLIMATOR	Complete with 30 sec. timer and cross indication line. A crossing point of 2 laser beams makes it easy to confirm a center of radiographic field and exact SID even under sunlight
LINE CABLE	6 Meter long
HAND SWITCH	Two stage, deadman type with curled cable.( 3 Meter long at full extension )
NET WEIGHT	X-ray unit : 12.5lbs Carrying case : 6.6lbs
POWER REQUIREMENT	AC 120 V / 20A
LINE VOLTAGE ADJUSTMENT	Automatic : possible with AC 70 V
OPTIMUM AMBIENT CONDITIONS	Temperature : 20 = 150C - Humidity : 69= 20%

**RATING:** ·30mA/40-42 kV/03-20 mAs  
· 20mA/43-62 kV/0.3-20 mAs  
· 15mA/63-80 kV/0.3-20 mAs



\*WHEN CONNECTED WITH DR SYSTEM, mAs. 13mAs WITH 63kV or more is possible.

**TELEVERE**  
SYSTEMS

101 E. Milwaukee St. Ste. 405 Janesville, WI 53545 1.800.385.9593